

INFINITY HS

Dry Brite and Burnashable Floor Finish/High Gloss/
Hard Surface Protection

SPECIAL FEATURES

A strong duo of Infinity's low maintenance advantage with InfinityX's enhanced durability. Together, we have created Infinity HS, a Dry/Brite and Burnishable High Solids floor finish. With the best of both worlds, Infinity HS is a shining combination of a low maintenance floor system, enhanced durability and a high solid formula which ultimately achieves extended floor burnishing cycles. Yes, Infinity HS truly embodies complete facility solutions.

DIRECTIONS

For best results, strip floors with PS Infinity Stripper, neutralize and clear water rinse. Check pH of floor to ensure it is neutral. For porous floors, new floors, or high traffic areas apply 4-5 coats of PS Infinity HS. For non-porous floors, simply apply 4 coats of PS Infinity HS Floor finish. For re-coating, clean floor thoroughly with PS Floor Cleaner, rinse and apply 1 to 3 coats of PS Infinity HS floor finish. Burnishing is not required. Restore with regular cleaning use of PS Floor Cleaner.

STRIP, NEUTRALIZE, RINSE, 4-5 INFINITY COATS

Manufactured by:
Ultra Chem Labs Corp.
www.ultrachemlabs.com
Tel-909-605-1640
Fax-909-605-1068
4581 Brickell Privado St
Ontario, CA 91761

Properties

Appearance: Milky white
Finish Type: Acrylic
Polymer (Super Durable)
VOC's: 4 gm/L
Solid Content: 24%
pH: 8.5
Weight/Gallon: 10 lb
Coverage:
1500-2500 sq. ft./gallon
Soil Resistance: Excellent
Drying Time: 15-45 minutes
(depending on humidity)
Color of Dry Film: Water Clear
Application Temperature:
50 degrees F (Minimum)
Storage Temperature:
40 degrees F - 85 degrees F
Storage Stability:
1 year under normal conditions
Freeze Thaw Stability:
Passes one cycle

INFINITY exceeds Slip
Resistance standards when
tested according to ASTM
D3052-87: 0.5
(Slip Resistant)