

INFINITY X

Burnishable Floor Finish/Extra High Speed
Super Durable Floor Protection

SPECIAL FEATURES

- Burnashable
- Extra High Speed drying and curing
- High Gloss and Durability/Pliability
- Does not discolor or yellow
- Easy to use, clean and maintain
- Savings on time/chemicals/labor

DIRECTIONS

- For best results, strip floors with PS Infinity Stripper, neutralize and clear water rinse.
- Check pH of floor to ensure it is neutral.
- For porous floors, new floors, or high traffic areas apply 2 coats of PS Infinity Sealer and 4 coats of INFINITY-X
- For non-porous floors, simply apply 3-5 coats of INFINITY-X without any Sealer.
- For re-coating, clean floor thoroughly with PS Floor Cleaner, rinse and apply 1 to 3 coats of INFINITY-X.
- Burnish if desired. Burnishing will speed up curing process
- Restore with regular cleaning use of PS Floor Cleaner.

STRIP, NEUTRALIZE, RINSE, 3-5 INFINITY COATS AND BURNISH

Manufactured by:
Ultra Chem Labs Corp.
www.ultrachemlabs.com
Tel-909-605-1640
Fax-909-605-1068
4581 Brickell Privado
Ontario, CA 91761

Properties

Appearance: Milky white
Finish Type: Acrylic Polymer
(Super Durable)
VOC's: 4 gm/L
Solid Content: 20%
pH: 8.5
Weight/Gallon: 10 lb
Coverage:
1500-2500 sq. ft./gallon
Soil Resistance: Excellent
Drying Time: 15-45 minutes
(depending on humidity)
Color of Dry Film: Water Clear
Application Temperature:
50 degrees F (Minimum)
Storage Temperature:
40 degrees F - 85 degrees F
Storage Stability:
1 year under normal conditions
Freeze Thaw Stability:
Passes one cycle

INFINITY 2 exceeds Slip
Resistance standards when
tested according to ASTM
D3052-87: 0.5
(Slip Resistant)