

# LOW LUSTER FLEX GOLD

Highly Durable Low Gloss/ Chemical Resistant/Flexible  
Floor Finish/Metal Free/26% Solids

## PRODUCT DESCRIPTION

Low Luster Flex Gold is a low gloss floor finish(matte sheen) that is environmentally conscious, chemical resistant and highly durable. Low Luster Flex Gold possesses exceptional clarity, excellent durability and is ideal for facilities where low gloss/low maintenance is preferred. Low Luster Flex Gold's durable dual acrylic copolymer base allows for easy repairs during application, resists black heel marks, pad burns and soil embedment. Being free of harmful metals and styrene, Low Luster Flex Gold will not discolor or yellow, is an environmentally safer finish option and is easy to clean and maintain.

With proper maintenance of Ultra floor finishes, stripping cycles can be dramatically reduced or eliminated. Overall, Low Luster Flex Gold provides the ideal solution for facilities that require a natural finish appearance and long-term protection for all hard walking surfaces.

## POWER OF TECHNOLOGY: INTERNAL THERMAL CATALYST

Internal Thermal Catalyst Technology allows Ultra polymer technology to dry from the bottom up versus conventional top down drying. The difference in technology provides two major procedural advantages: Extra fast drying time and easy walk-on repairs.

## NON STYRENE POLYMER TECHNOLOGY

Styrene is a known carcinogen that causes floor finishes to yellow or discolor. Unlike conventional finishes, Ultra finishes do not contain any styrene. Using an advanced Acrylic dual polymer technology, Ultra Chem Labs' finishes are environmentally safer, sustain high levels of durability, are easy to maintain and do not discolor or yellow. With proper maintenance of Ultra floor finishes, stripping cycles can be dramatically reduced or eliminated.

## FEATURES EFFICIENT:

- Low Gloss (Matte Finish)
- Low maintenance
- Highly Durable
- Fast Dry times (15-45 min) depending on humidity and ventilation
- Low odor
- Does not discolor or yellow
- Easy to apply

For best results, all UCL finishes are required to be used with Ultra's Cleaner and Conditioner for maintenance and restoration purposes. If any other manufactured products besides Ultra's Cleaner and Conditioner are used on UCL finished floors, Ultra Chem Labs will not be responsible for any indirect, direct or consequential damages. Furthermore, the products in question will be void of any standard product warranties. For more information, please request information on our standard product warranty.

Floor Care

ULTRACHEM LABS



Internal Thermal Catalyst



Non-Styrene Polymer

## PROPERTIES

Physical Form: Milky white liquid  
VOCs: 4gm/L  
Odor: Low  
pH: 8.5 +/- 0.5  
Solids: 26%  
Application Temperature:  
50 degrees F (Minimum)  
Storage Temperature:  
40 degrees F - 85 degrees F  
Film Color: Colorless  
Shelf life: 2 years in an unopened  
container  
Freeze/Thaw Stability:  
Do not freeze  
Dilution Ratio: Ready to use

# LOW LUSTER FLEX GOLD

## ENVIRONMENTALLY CONSCIOUS

- Meets third party environmental criteria regarding reduced toxicity, biodegradability, packaging and other characteristics focused on creating a more sustainable environment.
- Metal Free
- Styrene Free
- Low VOC's

## ECONOMIC

- Coverage at an average of 1500-2000 sq ft/gallon

## DIRECTIONS

1. For best results, strip floors or deep scrub with Ultra Green Stripper
2. After stripping floors, neutralize and clear water rinse and allow floor to dry. Check for pH of floor to ensure neutral pH levels. Neutralization is not required after deep scrub preparation.
3. For porous floors, new floors or high traffic areas apply 4-5 coats of Low Luster Flex Gold with a finish mop or applicator.
4. Allow for 15-45 min drying time depending on humidity
5. For re-coating, clean floors thoroughly with Cleaner and Conditioner, rinse and apply 1-3 coats of Low Luster Flex Gold. Restore with regular cleaning use of Cleaner and Conditioner.

## PERFORMANCE DATA

Drying time: 15-45 min (depending on humidity and ventilation)

Initial Gloss Level: 30-40

Slip Resistance: Low Luster Flex Gold exceeds Slip Resistance standards when tested according to ASTM D3052-87: 0.8

Chemical Resistancy:

Excellent: Cranberry juice, coke, orange juice, soy sauce, wine

Good: Coffee

Fair: Ammonia, bleach, hydrogen peroxide

Poor: Stripper, hand sanitizer, iodine, mustard

Available in 1 gal bottle, 5 gal pail, 55 gal drum



Please Recycle Container

Notice: Our only obligation shall be to replace or pay for any material proved defective. Beyond the purchase price of materials supplied by us, we assume no liability for damages of any kind and the user accepts the product "as is" and without warranties, expressed or implied. The suitability of the product for an intended use shall be solely up to the user.

Aviso: Nuestra única obligación será la de reemplazar o pagar por cualquier material probado defectuoso. Más allá del precio de compra de los materiales suministrados por nosotros, no asumimos ninguna responsabilidad por daños y perjuicios de cualquier tipo y el usuario acepta el producto "tal cual" y sin garantías, expresas o implícitas. La aplicación y uso específico del producto depende exclusivamente del usuario.

## Floor Care

# ULTRACHEM LABS



\* Ultra Chem Labs awards its internal Environmentally Sustainable Seal to products that meet third party environmental criteria regarding reduced toxicity, biodegradability, packaging and other characteristics focused on creating a more sustainable environment.

**FOR MORE INFORMATION**

**CALL: 909-605-1640**

**EMAIL: CS@ULTRACHEMLABS.COM**

**WWW.ULTRACHEMLABS.COM**

**ULTRA CHEM LABS CORP  
4581 BRICKELL PRIVADO  
ONTARIO, CA 91761  
UNITED STATES**