MATERIAL SAFETY DATA SHEET



SECTION 1 - CH	EMICAL PROD	OUCT AND	COMPAN	IY IDE	NTIFICA	TION	
Product Identifier SLAM DUNK PLUS V						WHMIS Classification:	
Product Use: High performance en		/wood seal an	d finish				
Manufacturer's Name: ULTRA CHEM LABS	CORP			Suppliers Name			
Street Address: 4581 BRICKELL PI	RIVADO			Street Addr	ress		
City: ONTARIO	Province:/ State CA			City			Province
Zip Code: 91766	Emergency Telephon 1-800-535-50			Postal Code	le	Emergency Telephone	
Date MSDS Prepared: MARCH 2015		MSDS Prepared by: ULTRA CHEM LABS CORF		ORP		Phone Number: 909-605-1640	
SECTION 2 - CO	MPOSITION / I	NFORMATI	ION ON I	NGRE	DIENTS		
Hazardous Ingredients (specific)		%	CAS Num	nber	LD ₅₀ of Ingredient (specify species and route)		LC 50 of Ingredient (specify species)
PROPYLENE GLYCOL		3.33	57-55-6 2		22,000 m	g/kg (oral, rat)	20,800 mg/kg (dermal, rabbit)
TRIBUTOXYETHYL PHOSPHATE PLASTICISER		1.92	78-51-3 5000		5000 mg	ı/kg (oral, rat)	> 500 g mg/kg (dermal,rabbit)
ACRYLIC P	OLYMER	40	N/AV		10,000 mg/kg (oral,rat)		N/AV
WATI	ER	54.75	7732-1	18-5	14,000 m	g/kg (oral, rat)	N/AV

SECTION 3 - HAZARDS IDENTIFICATION

Route of Entry	Skin Contact 🗇	Skin Absorption 🗇	Eye Contact	Inhalation 🗇	Ingestion
[Emergency Overview]	Wear protectiv	e gloves and suitable o	clothing.		
WHMIS Symbols] Class D - Poisonous and Infectious Material Division 2 Materials Causing Other Toxic Effects					
[Potential Health Effects] Prolonged or repeated exposure can cause skin drying.					

SECTION 4 - FIRST AID MEASURES

in Contact /AP
e Contact lush with copious amounts of potable water eek medical attention immediately
nalation /AP
gestion live large amounts of water to dilute. Seek Medical Attention

Product Identifier: SLAM DU	NK PLUS WOOD	FINISH		Page	≥ 2/4
SECTION 5 - FIRE FIGH	TING MEASU	RES			
Flammable Yes D No	If yes, unde	er which conditions?			
Means of Extinction As for surrounding fire. Norma	al Fire - Fighting F	Procedures			
Flashpoint (°C) and Method		nmable Limit (% by volume)	Lower Flamma	able Limit (% by volume)	
NONE Autoignition Temperature (°C) NONE		Data - Sensitivity to Impact		a - Sensivity to Static Discharge	
Hazardous Combustion Products Oxides of Carbon					
^[NFPA] NONE					
SECTION 6 - ACCIDEN	TAL RELEASE	E MEASURES			
Leak and Spill Procedures Large spill: Dike with absorbe Rinse with water and let dry.	nt, collect in drum	, then dispose.			
SECTION 7 - HANDLING	G AND STOR	AGE			
Handling Procedures and Equipment NORMAL HANDLING PROCI	EDURES, AVOID	EYE AND SKIN CC	NTACT		
Storage Requirements COOL, DRY, WELL VENTILA	TED AREA. REC	OMMENDED TEM	PERATURE 15	SoC OR 59°F.	
SECTION 8 - EXPOSUR	RE CONTROL	/ PERSONAL P	ROTECTION	N	
Exposure Limits N/AV ACGIH TLV	OSHA P		OTHER (speci	ify) 🗇	
Specific Engineering Controls (such as ventilation Normal ventilation	n enclosed process)				
Personal Protective Equipment Gloves Respirator	Eye 🗇	Footwear 🗇	Clothing	☐ Other	Ø
If checked, please specify type Neoprene or rubber gloves					

Product Identifier: SLAM DUNI	K PLUS WOOD FINISH		Page 3/4	
SECTION 9 - PHYSICAL A	AND CHEMICAL PRO	OPERTIE	S	
Physical State Emulsion	Odour and Appearance Mild odor; milk white s	solution	Odour Threshold (ppm) N/AV	
Specific Gravity	Vapour Density (air = 1) < 1		Vapour Pressure (mmHg) 17 mmHg	
Evaporation Rate > 1	Boiling Point (°C) >100°C		Freezing Point (°C) <0°C	
он 3.5 <u>+</u> 0.5	Coefficient of Water / Oil Distribution 100% water soluble		[Solubility in Water]	
SECTION 10 - STABILITY	AND REACTIVITY		•	
Chemical Stability Yes No D Incompatibility with Other Substances Yes No D		If no, under which conditions? If yes, which ones? Strong oxidizing agents - eg. Bleach		
Reactivity, and under what conditions?				
lazardous Decomposition Products				
252510N 44 TOVICOLO	POLOAL INFORMATIO			
SECTION 11 - TOXICOLO	GICAL INFORMATION	<u> И</u>		
Effects of Acute Exposure				

Effects of Acute Exposure		
Eye contact will cause irritation		
Effects of Chronic Exposure		
N/AP		
Irritancy of Product Contact with eyes/skin		
Skin Sensitization N/AV	Respiratory Sensitization	
Carcinogenicity -IARC	Carcinogenicity - ACGIH	
NO	NO	
Reproductive Toxicity	Teratogenicity	
N/A	N/A	
Embryotoxicity	Mutagenicity	
N/AP	N/A	
Name of Synergistic Products / Effects		N/A

Product Identifier: SLAM DUNK PLUS WOOD FINISH Page 4/4

SECTION 12 - ECOLOGICAL INFORMATION

Aquatic Toxicity Molibity= N/A	Persistence= N/A	Bioaccumulative = N/A	
--------------------------------	------------------	-----------------------	--

Aquatic Toxicity: Low potential affect on Aquatic organism and secondary waste treatment microbial respiration. When diluted with a large amount of water, this material is released directly or indirectly into the environment and is not expected to have a significant impact.

THOD (G Oxygen G)= -1.9 COD (G Oxygen (G) = 1.9 BOD5 (G Oxygen (ML) = 0.14

Acute Aquatic effects Data: Ceriodaphnia Dubia LC 50 - 6 days (Ceriodaphnia) >10 LC 50 >10

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal

Rinse 3 times with water. Then offer recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by incineration, or if allowed by state and local authorities, by burning. If burned, stay away from smoke, according to local, state and federal government requirements.

SECTION 14 - TRANSPORT INFORMATION

Special Shipping Information: Normal procedures. Keep from fro	eezing.	
PIN N/AP		
TDG: N/AP	[DOT] NOT REGULATED	
[IMO] N/AP	[ICAO] N/AP	

SECTION 15 - REGULATORY INFORMATION

Class D Div 2 Materials Causing Other Toxic Effects	[OSHA] N/A
INI/A	[TSCA] N/A

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by CPR

SECTION 16 - OTHER INFORMATION

Notice to Reader:

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.